

HMK® S242

Enhancing Impregnator

Reduces penetration of water and dirt on polished, honed and textured finishes. Enhances color. Solvent based. For interior and exterior use.



HMK® S242 is a ready to use solvent based impregnator for use on all natural stone surfaces (soft and hard), agglomerates, reconstituted stone and terrazzo, and can be used on polished, honed and textured surfaces. By reducing water and dirt penetration, regular maintenance is facilitated. Algae, fungus and other problems occurring with exterior installations are reduced. Color enhancement will bring out the grain and structure of the stone. HMK® S242 is especially suited for wall and floor surfaces. Vapor permeation is only slightly diminished. Please note that HMK® S242 is not effective against oil and grease. For exterior and interior use.

Important: Clean surface thoroughly before treatment using HMK® R155 Intensive Cleaner (diluted) followed by a flood rinse with water and allow at least 24 hours to dry (max residual moisture of 2-4%) before sealing. If under floor heating exists, switch it off and allow the surface to cool to room temperature.

Instructions: Apply HMK® S242 generously and evenly to a chemically clean and dry surface with a natural bristle paint brush or the HMK® Z950-HMK Z951 brushes. One saturating, wet-on-wet application is usually sufficient depending on porosity of the stone. Thoroughly remove excess before drying on the surface. For more absorbent surfaces additional applications may be required. Subsequent applications may be done within fifteen minutes of the initial application, but it is best to wait 24 hours between applications to best determine saturation level. Smears or imperfections left after the application process can be removed using a soft clean cloth moistened with HMK® S242 and buffing.

Do not walk on the treated surface until 4 to 6 hours after treatment is completed. Resistance to dirt and water is developed over 24 hours. Protect surface from rain and humidity for 12 hours. Do not apply to rubber, plastics, lacquered or varnished surfaces and solvent intolerant materials. Remove all foodstuffs from the area to be treated before work is commenced. Once dry the residual material is not harmful to health. For regular cleaning and continued protection use HMK® P324 Liquid Stone Soap.

Coverage: About 50 to 220 square feet per liter depending on the nature of the surface.

Warning: Chemical product. Contains turpentine substitute. Flammable. Keep away from heat, sparks and flame. Harmful or fatal if swallowed or inhaled. Ensure the area to be treated is adequately ventilated. Avoid eye/skin contact. If exposed wash/flush with water and seek medical attention immediately. Keep out of the reach of children. See Material Safety Data Sheet for more detailed information. Do not use the product in temperatures below 50 and above 80°F.

Packaging: 12 x 1L tins per box; 2 x 5L tins per box

Storage: Store in a cool place and keep lid tightly closed.

Testing: Always test the product in an inconspicuous area to evaluate suitability, coverage and performance.

Limitation of liability: The liability of HMK® Moeller Stone Care and/or ACI International for defective products and any claims for damages whatsoever is limited to the purchase price of the products. HMK® Moeller Stone Care and/or ACI International shall not be liable for any consequential damages. No other warranty or representation is made or implied.